Nu 1 SHOOTING WET END.xlsx						Date:		12-Jan-2023		
						Technician:			Tempest	
Company:	TFL									
Type of Leather:	of Leather: Shoe Upper & Leather Goods						•			
Aim of Trial:	ABRASIVATO					Color:		18-0513		
							Piece count:			
Project - N°:	1 SHOOTING					Substand	e:		1-1,	
Material:	calf wb					Weight:	•			
% refer to:	shaved weight					Drum - N°:				
Operation	Add	%	Weight	Product	Temp.	Dilution	Time	Control		
operation	Auu	70	in kg	1100000	in °C	(1 : x)	in min	o ona or		
		300,00		water	40°C	(				
		1,00		formic acid						
		0,50		PELTEC ADN			30			
drain wash		- ,								
		100,00		water	40°C					
		6,00		RETINGAN RLF						
		1,00		CORIPOL DX1202			30			
		5,00		BLANCOROL RC						
		5,00		CHROMOSAL B			120	automatic		
drain								morning p	H: 3,8	
		150,00		water	35°C					
		2,00		TANIGAN PAK						
		1,00		sodium formate			30			
		0,40		sodium bicarbonate			10		0	
duala waab		3,00		BAYTIGAN AR			40	pH: 4,6-4,	8	
drain wash		100,00		water	30°C					
		1,00		MAGNOPAL DP	30 0		5			
		1,00		CORIPOL DX1202			5			
		5,00		LEVOTAN RP						
		12,00		TANIGAN GS						
		3,00		BAYKANOL PFM			20			
		2,00		TANIGAN SR						
		x		SELLAFAST dyestuffs			30			
		5,00		RETINGAN R7			60			
		100,00		water	50°C					
		х		formic acid			30			
drain wash										
		100,00		water	50°C					
		3,00		CORIPOL DX1202				ļ		
		3,00						ļ		
	$\rightarrow$	4,00		LUBRITAN SPE						
	-+	1,00		RODA OIL 1449			60			
drain		0,50		formic acid			30			
drain										
Mechanical Operation:						s Informati	on <sup>,</sup>	L		
set out, vacuum di		0°C					*****************			
						n Tim			9 hrs 05	
						Running Time:			8 hrs 05 min	

Our application recommendations are in line with our present state of knowledge. They do not, nowever, exempt the customer's sphere of responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery. Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application.