

Product Information

Finishing



Edition 2013

RODA[®] Care 5754 – Pre-bottom for upgrading

Product properties	RODA [®] Care 5754 is a ready-to-use compound specifically formulated to cover defects present in full grain leather, particularly suitable for nappa and special smooth finishing for upholstery and automotive articles. The main advantages obtained by using RODA [®] Care 5754 are: Excellent sealing capacity resulting in good coverage of small and medium defects on full grain leather without any overloading; Good adhesion; Enlargement of the usable surface area, which results in greater exploitation of the finished leather; Application with modern and efficient systems, which enable a high volume of leather production
Application	RODA [®] Care 5754 is applied by reverse roller coater with the quantity employed varying from 20 to 30g/m ² according to the type of leather. After RODA [®] Care 5754 has been applied, the leather should be left to set 12 hours before proceeding with the finishing operations.
Chemical nature	Formulated by water based acrylic polymers, polyurethanes and fillers
Appearance	White opaque paste
Solids	32.5 – 34.5 %
pH	8.5 – 10.0
Viscosity range	10,000-14,000 (sp6, rpm 20 at 25°C) Brookfield Viscometer Please pay attention: Climatic and transport conditions could cause variations on the viscosity range declared in this document.
Density range	0,840 – 0,860 g/cm ³ at 20°C
Charge	Anionic
Storage	The product can be stored in its original packaging between 5°C and 35°C for 6 months.
Safety	For safety information see the safety data sheet

Regarding toxicological and ecological data see the safety data sheet of above product.

RODA[®] is a registered or filed trademark owned by or licensed to TFL in most countries.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application