

# Product Information

## Finishing



Edition 2012

### RODA® Tec AW – NMP-free and NEP-free Protector against Soiling

#### Product properties

RODA® Tec AW is a water-based formulation based on touch modifiers and matt binders. RODA® Tec AW is an effective soil protector. Besides this, it maintains the soiling resistance of the leathers finished with our Anti-soiling top coat, system based on RODA® FIX SR04, and it also gives to the leather a pleasant and waxy touch.

When applied 3 or 4 days after the fixation with our Anti-soiling System based on RODA® Fix SR04, RODA® Tec AW allows also an improvement of the anti-soiling properties of the leather.

RODA® Tec AW is suitable for all kind of leather articles.

#### Application

RODA® Tec AW can be applied by padding it both as it is and/or diluted into water in a ratio of 1:1, with circular movements using a very soft sponge, It can be also applied by spraying it prediluted with water in a ratio of 1:1.

We recommend to let the leather rest for one day after application of RODA® Tec AW in order to complete the drying.

#### Chemical nature

Formulation of water based touch modifiers and matt polymers

#### Appearance

Opaque white liquid

#### Solids

11.0 – 13.0 %

#### pH

7.0 – 9.0

#### Charge

#### Storage

The product can be stored in its original packaging between 5°C and 35°C for 12 months.

#### Safety

For safety information see the safety data sheet

Regarding toxicological and ecological data see the safety data sheet of above product.

RODA® is a registered or filed trademark owned by or licensed to TFL in most countries.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application