

Product Information

Finishing



Edition 2005

RODA® Wax KCF 699 – Wax

Product properties	<p>RODA® Wax KCF 699 is a highly shiny and glossy film forming synthetic Wax with a high melting point.</p> <p>Due to its filling power it is utilized in the polishable bottoms whilst it reduces the stickiness in the basecoats.</p> <p>It can be used either in the topcoats for glazed finishing or to improve wet rub fastness and hot iron resistance.</p>
Application	<p>RODA® Wax KCF 699 is applied by spray guns in the ratio of 50-100 g/l in a polishable pre-bottoming, whilst in the top coat it should be added in the ratio of 20-30% of the top coat weight.</p>
Chemical nature	Formulated by water based waxes
Appearance	Light yellow opalescent liquid
Solids	12,5-14,5%
pH	10.5 – 11.5
Charge	Anionic
Storage	The product can be stored in its original packaging between 5°C and 35°C for 12 months.
Safety	For safety information see the safety data sheet

Regarding toxicological and ecological data see the safety data sheet of above product.

RODA® is a registered or filed trademark owned by or licensed to TFL in most countries.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application