

Product Information

Wet-End



SELLASOL® FTF – Universal, economical filling agent

Edition 2009

Features	<p>SELLASOL® FTF is a light brown powder based on selected natural substances.</p> <p>Lightfastness: Very good</p> <p>Handling & storage stability: Wear gloves and goggles during handling & CLOSE SACKS TIGHTLY AFTER USE. Can be stored for about 1 year (from date of production) if kept in a dry place.</p> <p>Stability in chrome tanning floats: Stable.</p> <p>Method of application: SELLASOL® FTF is preferably added undissolved to the drum.</p>
Benefits	<p>SELLASOL® FTF is easy to use. It does not need attention to pH adjustment in order to make it work.</p> <p>SELLASOL® FTF is free of formaldehyde thereby making it suitable for automotive leather, (chrome tanned and wet white).</p> <p>SELLASOL® FTF is also a natural scavenger which is effective in reducing free formaldehyde in the leather.</p> <p>SELLASOL® FTF due to an optimized combination of specially selected raw materials, it imparts to leather a nice balance between fullness and tightness.</p> <p>SELLASOL® FTF has no negative effect on tear strength.</p> <p>SELLASOL® FTF has a good dispersing action and supports good dye levelness.</p> <p>SELLASOL® FTF supports economical filling.</p>
Application	<p>SELLASOL® FTF can be applied to wet blue and wet white leather from bovine and small skins.</p> <p>SELLASOL® FTF is best added dry, about 20 minutes before the main fatliquor. This ensures the best filling effect in the loosest parts of the hide (belly area and flanks) and will thus positively support the fatliquoring process & ensure a tight grain.</p> <p>SELLASOL® FTF can also be applied during or even prior to the retannage.</p>

Regarding toxicological and ecological data see the safety data sheet of above product.

SELLASOL® is a registered or filed trademark owned by or licensed to TFL in most countries.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application

SELLASOL® FTF – Universal, economical filling agent

The following applications are recommended, depending on the requested article:

Box leather: 4 % - 6 % SELLASOL® FTF

Automotive / upholstery: 2 % - 4 % SELLASOL® FTF

Sheepskin leather: 2 % - 4 % SELLASOL® FTF

(all %ages are based on shaved weight)

Trade Form at 20°C	powder
Appearance at 20°C	light brown powder
Dry content (%)	approx 95
pH-value (10%)	approx 6.0

This information is for guidance only.
A Product Specification is available on request.

Regarding toxicological and ecological data see the safety data sheet of above product.

SELLASOL® is a registered or filed trademark owned by or licensed to TFL in most countries.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application